

# CFW10

GUIA ESPECIFICACIÓN		CFW10									
Potencia (HP)	In Motor 220 V		Corriente Nominal Máx. (A)	Entrada	Tensión de Alimentación (Vca)	Transistor de Frenado	Talla	Versión	Dimension (Alto x Ancho x Prof. mm)	Protección con Guardamotor MPW	
1	3,15	2586101305	4	Monofásica	200 - 240	NO	1	Estandar	132x95x121	2012428128	MPW40-3 (10 - 16 A)
		2417111465	4	Monofásica	200 - 240	NO	1	Plus	132x95x121	2012428128	MPW40-3 (10 - 16 A)
2	5,83	2417111466	7,3	Monofásica	200 - 240	NO	2	Plus	161x115x122	2012428129	MPW40-3 (16 - 20 A)
3	8,49	2417111467	10	Monofásica	200 - 240	NO	3	Plus	191x115x122	2012428133	MPW40-3 (20 - 25 A)

Obs.: Verision PLUS con potenciómetro incorporado de fabrica  
 POTENCIAS CALCULADAS EN BASE A MOTORES WEG: 4 POLOS - W22 IP55 IE1 - EFICIENCIA ESTANDAR 50 Hz - 380 V / 50 Hz

INTERFAZ I/O				
	Std	Clean	Plus	Cold Plate
Entradas Digitales	4	4	4	4
Salidas Digitales	-	-	-	-
Salidas a Relé	-	1	-	-
Entradas Analógicas	1	-	1	1
Salidas Analógicas	-	-	-	-